Power Steering Cleaner

Power-Steering Cleaner

Product properties

Highly active special cleaning formula to remove contami-nations throughout the whole system. Because of special lubrication components all parts are protected while the system is being cleaned. It protects against high temperatures and provides a low-noise operation. Therefore the fuel consumption is optimized.

Area of application

In all power steering systems, differentials, differential gears

Application

Before changing of power steering fluid drain approx 20% of its content. Afterwards add the power steering cleaner. The appropriate formula of usage is 150 ml cleaner per litre power steering fluid. In order to guarantee an effective cleaning it is necessary to move the steering approx 25 times to the left and to the right. Afterwards drain the power steering fluid completely and refill it according to the manufacturer's guidelines. The product can be easily recycled with old oil.

Attention:
Harmful: may cause lung damage if swallowed. Harmful to aquatic organism, may cause long-term adverse effects in the aquatic environment. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label.

Consumption

100 ml for 3 ltr. Oil. Mix Ratio 1:30

Reaction time

Approx. 5-10 Minutes

Technical data

Physical state: liquid
Colour: yellow
Odour: aromatic
Initial boiling point and boiling range: 180 - 220 °C
Flashpoint: 63 °C
Ignition temperature: > 200 °C
Vapour pressure (at 68 °F): 20 hPa
Density at 68 °F: 0.82 - 0.90 g/cm³
Water resistant

Available size	Item no.	PU
100ml	60049	24
1L	60046	12
5L	60040	4
10L	60044	1
20L	60041	1
200L	60042	1

Our information is based on careful examination and may be considered as reliable. Hower, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.

CTP GmbH
Saalfelder Straße 35 h
07338 Leutenberg
Germany
Tel.: +49 (0)36734 230-0
Fax: +49 (0)36734 230-22
www.bluechemgroup.com
www.ctp.de